








EC4260 48 Specifications		
Parameter	Unit	Value
Rated Power	W	60.00
Rated Voltage	VDC	48.00
Continous Stall Torque	N-m	0.12
Max Torque	N-m	0.24
Rated Speed/Max Speed	rpm	4000/6800
Rated Current	A _(peak)	1.82
Max.Current	A _(peak)	3.63
Ke : Back EMF Constant	V _(peak) /krpm	7.00
Kt : Torque Constant	Nm/A _(peak)	0.066
Resistance	Ω	2.10
Inductance	mH	3.00
Moment of Inertia	gcm ²	48.00
Number of Poles	#	8.00
Mass	g	440
Winding Type	3-phase	
Hall Sensors	120° electrical spacing	
Pole Count	8	
Shaft Runout	.025 mm	
Radial Play	.02 mm @ 450 g	
End Play	.08 mm @ 450 g	
Max Radial Force	28 N @20 mm from flange	
Max Axial Force	10N	
Insulation Class	B	
Dielectric Strength	500 VDC for 60s	
Insulation Resistance	>100MΩ, 500 VDC	

HALL SENSORS AWG 26				
5VDC	GND	A	B	C
RED	BLK	BLU	GRN	WHT

MOTOR CABLE AWG 22		
A	B	C
YEL	RED	BLK





SECTION A-A



THIS DRAWING CONTAINS PROPRIETARY INFORMATION OF THE ORBEX GROUP AND MAY NOT BE IN WHOLE OR IN PART DUPLICATED OR DISCLOSED OR USED FOR MANUFACTURE OF ANY PART DISCLOSED HEREIN WITHOUT WRITTEN PERMISSION OF THE ORBEX GROUP.

CONFIDENTIAL



		UNLESS OTHERWISE SPECIFIED: DRAWING SYMBOLS & TOLERANCES PER ANSI Y14.5 DIMENSIONS ARE METRIC TOLERANCES: DECIMALS LINEAR ANGULAR .X ±0.2 ±0.5DEG .XX ±0.02 ±0.2DEG .XXX ±0.005 ±0.01DEG		INTERPRET GEOMETRIC TOLERANCING PER: ANSI Y14.5	
MATERIAL SEE CHART		FINISH Clean		DRAWN Sun KPO 11/25/2019	
SIZE B		PRT. NO. 100112		REV B	
SCALE: 1:1		SHEET 1 OF 1			